

SECURELY EXCHANGE C2 MILITARY INFORMATION

The Arbit C4ISR gateway allows you to securely exchange C2 information between coalition forces on the battlefield, supporting both automated and manual release as well as import of data.

SECURE AND TIMELY DATA EXCHANGE

Smaller or larger military formations that have deployed cross domain solutions to obtain the highest security, still have the essential need to exchange timely C2

information between coalition forces. The Arbit C4ISR gateway supports safe and fast data exchange, supporting both automated and manual release and import of data.

Since the import and export of data is subject to many security procedures and regulations, the Gateway supports a full set of security procedures that can be required for data exchanges.

Typically, classifications, markings, release ability, formats, and origin of data must always be verified and checked before data can be released or exchanged. In addition, some types of information exchanges are extremely time sensitive, such as blue force tracking and cross domain call for fire.

The Arbit C4ISR gateway allows you to set validations and checks to meet your security profile, including release procedures (two-factor release), data content validation, validation of signing, classification, and other filters such as multiple virus scanning.

Arbit C4ISR Gateway is built on Arbit's hardware-based Data Diode technology and therefore offers a continued network separation with no backflow possible.

The Arbit C4ISR gateway can be delivered in two variants – a server room version and a rugged version (only hardware is different). The rugged C4ISR getaway is designed and built to operate in the battlefield under the most challenging conditions. All units are 1U 19"/2 and a full gateway is only 3U (UPS and power supply excluded) equipped with NATO standard connectors and designed for vehicle mount.

Tested to operate in the battlefield

Verification of Data Signatures

Two factor authentications

Open API for custom content filters



FEATURES

SUPPORTED PROTOCOLS



The Arbit C4ISR Gateway platform allows implementation of different security profiles and offers a range of filters and add-ons. The most important feature is that the robust and open API of the Gateway allows you to program and build your own national security profile independent from any contractor support. This is the highest level of security you can get - you own the data as well as the processes.

- S/MIME mail integration
- Open API for sending transactions (C++ and Java)
- SitaWare
- MIPS
- **ASCA**
- SYSTEMATIC one-way communication



Logging

Provides full audit log and syslog.



Offers open API for building custom content filters (C++ and Java).



Malware **Protection**

As an OPSWAT partner, the C4ISR Gateway integrates with OPSWAT MetaDefender multi anti-malware scanning and CDR.



Verification of Data **Signatures**

Uses signing technology to securely identify the source of released data. Only approved source systems or individuals can sign data which is then allowed to pass through the gateway.



Two-factor **Authentication**

Supports signing as standard and NATO Clearing house functions such as Releasing and Clearing officer.





SIZE

components

Data diode 1U 2x19"/2

POWER

- Based on 1U. 19"/2 Both Gateway and Data
 - Server < 200 W
 - Diode < 170 W
 - Full Gateway less than



WORKING CLIMATE / TESTED ENVIRONMENTS

- Temperature shock
- Salt/fog
- Vibration
- **EMC/EMI Environment**



SECURITY CERTIFICATION

The Target of Evaluation (TOE) ensures NO backflow is possible.

Server 1U 1x19"/2

units

Full gateway 3U 19"

- Diode will run on 12-24 V
- 800 W

ABOUT

Founded in 2006, Arbit specializes in cybersecurity solutions for organizations requiring the highest security. Arbit's solutions are deployed in top security networks throughout the world, including military organizations, police, and intelligence services.



Arbit Cyber Defence Systems ApS